

EASY WASH

DESCRIPTION

Moon Star easy wash is a superior-grade product that provides interior walls with long-lasting protection, rapid drying, great washability and maximum coverage. Its unique feature is the ability to remove all types of stains, making the wall look more stylish and elegant.

FEATURES AND BENEFITS

- Excellent scrub resistance
- Soft sheen, longer life
- Free from fungi and heavy metals such as lead, mercury, chromium etc.
- Available pleasing shades

USES

All exterior/interior walls, Cement plaster, concrete stone, brick, asbestos and all types of building boards.

TECHNICAL SPECIFICATION

Binder	: Pure acrylic Emulsion
Pigmentation	: Titanium Dioxide and Mineral extenders
Colorant	: Universal colorant
Solvent	: Water
Solid by weight	: 50%
Viscosity	: (5-6) thousand mPa.s
Sp. Gravity	: 1.15 – 1.25
Coverage	: 150-160 Square feet /Ltr/Coat (Depends on Surface)

Flammability	: Not applicable
Touch dry	: 30 minutes (At 30°C)
Hard dry	: 24 hours (recoat)
Clean up solvent	: Water
Thinner	: Clean Water
Sheen 600 Value	: Egg Shell
Shade / Color	: As per Moon Star Shade card, Color choice shade card and any customized shade

SURFACE PREPARATION

The surfaces must be clean, dry, and free from dirt, oily substance, fungus, saltiness and corrosion as well as old painted substances. For new walls make sure of perfect dryness. Then scrub well with stone. Next, make sure it is moisture free. Apply one coat of Moon Star water-based sealer after dryness. After 6-8 hours, when the sealer gets dried observe the surface condition. Then apply Moon Star wall putty if needed. Apply Moon Star Salt Sealer if the wall is salty. Apply another coat of sealer after 24 hours of finishing with sandpaper in order to prepare a suitable surface.

APPLICATION METHODS

Stir well after opening the container. It can be applied with a brush, roller or spray.

THINNING METHOD

For Brush Paint : Water = 2 : 1 (By volume)

For Roller Paint : Water = 3 : 1 (By volume)

Quality may not be ensured if diluted excessively. Two coats are enough for final finishing. Apply the next coat after 6 hours. Apply the water-mixed paint as soon as possible and rinse the materials used.

PACK SIZE

18.2 liters

3.64 liters

0.91 liters

PRECAUTIONS

- Keep away from children.
- If splashes enter the eyes, wash them with plenty of water.
- Emulsion-based material, should be protected from frost, heat or sunlight.
- It is non-flammable under normal conditions of use.
- Ensure good ventilation during application and drying.
- Prolonged skin contact should be avoided.

DISCLAIMER

The information given herein is based on our present knowledge and is believed to be reliable. We can't assume any responsibility since the usage conditions are beyond our control.