TECHNICAL DATA SHEET



LUXURY HIGH SHINE

DESCRIPTION

It is a water-based 100% pure acrylic interior wall finish that provides a silky sheen finish leaving a soft glow and smoothing splendor to the interior of the room. It provides a luxurious finish and posh silky glowing hallmark to your wall. This product is easy to clean & remains unmarred and unblemished for years.

FEATURES AND BENEFITS

- Excellent silky finish
- · High shine
- Resistance properties against fungi, heavy metal such as lead, mercury, chromium etc.
- Available pleasing shades

USES

All interior wall, Cement plaster, concrete stone, brick, asbestos and all types of building boards.

TECHNICAL SPECIFICATION

Binder : Pure acrylic Emulsion

Pigmentation : Titanium Dioxide and

Mineral extenders

Colorant : Universal colorant

Solvent : Water Solid by weight : 50%

Viscosity : (5-6) thousand mPa.s

Sp. Gravity : 1.15–1.25

Coverage : 160-170 Square feet

/Ltr/Coat (Depend on

Surface)

Flammability : Not applicable

Touch dry : 30 minutes (At 30°C)

Hard dry : 24 hours (recoat)

Clean up solvent : Water

Thinner : Clean Water

Sheen 600 Value: Semi-Glossy

Shade / Color : As per Moon star Shade

card, Color choice shade card and any customized

shade

SURFACE PREPARATION

The surfaces must be clean, dry, and free from dirt, oily substances, fungus, saltiness and corrosion as well as old painted substances. For new walls make sure of perfect dryness. Then scrub well with stone. Next, make sure it is moisture-free. Apply one coat of Moon Star water-based sealer after dryness. After 6-8 hours, when the sealer gets dried observe the surface condition. Then apply Moon Star wall putty if needed. Apply Moon Star Salt Sealer if the wall is salty. Apply another coat of sealer after 24 hours of finishing with sandpaper in order to prepare a suitable surface.

TECHNICAL DATA SHEET



APPLICATION METHODS

stir well after opening the container. It can be applied with a brush, roller or spray.

THINNING METHOD

For Brush Paint: Water = 2:1 (By volume)
For Roller Paint: Water = 3:1 (By volume)

Quality may not be ensured if diluted excessively. Two coats are enough for final finishing. Apply the next coat after 6 hours. Apply the water-mixed paint as soon as possible and rinse the materials used.

PACK SIZE

18.2 liters

3.64 liters

0.91 liters

PRECAUTIONS

- Keep away from children.
- If splashes enter the eyes, wash them with plenty of water.
- Emulsion-based material, should be protected from frost, heat or sunlight.
- It is non-flammable under normal conditions of use.
- Ensure good ventilation during application and drying.
- Prolonged skin contact should be avoided.